

<b>Product Name :</b> Cooling Tower	<b>Product Code :</b> KGLOB10121002
--	--



**Description :**

Cooling Tower

**Technical Specification :**

Features of the unit

- 1) cooling towers, housings are made of high strength glass fiber.
- 2) advanced internal design, excellent cooling effect, low noise operation, low energy consumption.
- 3) anti-corrosion and anti-harsh environment and strong ability to facilitate maintenance.
- 4) Mainly used in all sectors of the national economy, cooling, air conditioning heating furnace and condenser technology, injection molding machine series is particularly suitable for cooling water circulation.

Flow rate (m <sup>3</sup> /h)	Main dimensions (mm)	Water flow rate (m <sup>3</sup> /h)	Wind speed (m/s)	Electricity consumption (KW)	Weight (kg)	Water pressure (bar)	Piping size (mm)

	Tower body Height TH	maximum diameter MD	net weight	(mm)		Standard type		Low noise type		overflow water tube	Enter water tube	Out water tube			
				Shipped Row weight	Shipped Row weight	103Pa	Make up water tube								
6	1380	950	5.4	525	0.18	45	185	50	200	23	15	25	25	40	40
8	1550	950	7.2	600	0.18	50	195	55	210	23	15	25	25	40	40
10	1400	1195	9.1	600	0.37	60	300	66	320	24	15	25	25	50	50
12	1420	1200	10.8	600	0.37	65	310	70	330	24	15	25	25	50	50
15	1650	1200	12.8	730	0.56	85	350	96	370	24	15	25	25	50	50
20	1850	1450	17	730	0.75	110	520	120	550	26	15	25	25	80	80
25	1750	1650	21.3	730	0.75	125	560	136	585	26	15	25	25	80	80
30	1850	1650	26.2	890	1.5	155	600	160	620	28	15	25	25	80	80
40	1900	1850	34.5	890	1.5	200	960	210	1000	28	15	25	25	80	80
50	2000	2150	42.5	1150	1.5	260	1300	270	1350	29	20	25	25	100	100
60	2100	2150	51	1150	1.5	295	1420	300	1460	29	20	50	50	100	100
80	2400	2950	68.5	1450	2.2	560	1680	575	1720	29	20	50	50	125	125
100	2580	2950	85.2	1450	2.2	586	1750	595	1796	32	20	50	50	125	125
125	2580	2950	106	1450	2.2	610	1780	625	1800	32	20	50	50	150	150
150	3200	3320	128	1750	3.75	895	2100	910	2150	32	25	50	50	150	150
175	3600	4150	149	2135	5.5	1120	2890	1130	2910	38	40	80	80	200	200
200	3600	4150	170	2135	5.5	1230	2960	1250	3100	38	40	80	80	200	200
225	3700	4730	191	2430	7.5	1750	3900	1820	3960	38	40	80	80	200	200
250	3700	4730	213	2430	7.5	1900	4120	1920	4150	39	40	80	80	200	200
300	3900	5620	255	2740	11.0	2900	5950	2930	5980	43	40	80	80	200	200
350	3950	5620	298	2745	11.0	2950	5980	2980	6120	43	40	80	80	200	200
400	3980	5650	340	2745	15	3000	6120	3050	6160	43	50	100	100	250	250
450	4480	6650	383	3400	15	3860	9310	3880	9350	48	50	100	100	250	250
500	4480	6650	425	3400	15	4260	9860	4310	9920	48	50	100	100	250	250
600	4750	7620	510	3700	22	4920	12150	4950	12210	56	80	100	100	300	300
800	4750	7620	680	3700	22	5050	12350	5080	12385	56	80	100	100	300	300
1000	4950	860	850	5000	30	7860	16820	7890	16865	61	80	100	100	350	350