

Product Name :
Relief Water Distribution Kit 6 Taps

Product Code :
KGLOB22214098



Description :

Relief Water Distribution Kit 6 Taps

Technical Specification :

Water distribution kit (tap stand) to be used with collapsible water tanks. The stand is made of hot dipped galvanized steel pipes or hot rolled galvanized steel sections. All pipes should be threaded as per ISO 7 (the thread cutting oil must be non toxic type), and must be able to withstand rough handling during use.

- Four sturdy legs (or two "A" frames), each leg fitted with a drilled plate for holding down purposes.
- 1 x 1 ½" (40 mm) male threaded riser pipe.
- 1 Female threaded 2"-1 ½" (50 mm-40 mm) junction tee with closing(for the connection to the storage tank or to other tap stands).
- 2 male threaded Guillemin or Storz couplings.
- 1 central, horizontal distribution pipe.
- 6 x Male threaded tap pipes welded to the central distribution pipe.
- 7 x Female threaded ¾" (20 mm) self-closing taps. Minimum discharge rate per tap: 10 liters per minute at one meter head, operation range: Up to 4 bars.
- 2 x ¾" (20 mm) female threaded caps (for closing in case of repair of repair of faulty taps).
- 4 rolls of teflon tape (12 mm x 12 meters each).
- 4 plated pegs for fixing down of the tap stand, each 30 cm long, minimum diameter 12 mm.
- 1 piece of wire netting for concrete slab, 0.9 x 1.5 meters each.(Smaller pieces could be supplied to minimize the shipping volume, provided that the necessary overlapping of the net reinforcement is taken into consideration).