

Product Name :
Semi Automatic Carton Taping Machine

Product Code :
KGLOB10251027



Description :

Semi Automatic Carton Taping Machine

Technical Specification :

Phase Singhal Phase
 Voltage 220 v
 Material to be Packed Plastic
 Functions Motorized
 Power 220
 Machine Type Semi-Automatic
 Automatic Grade Semi-Automatic
 Driven Type Electric
 Carton Dimensions 600 x 500
 Capacity Variable
 Material M.S. Body
 Dimension 8 feet x 24 inch x 5 feet
 Power Supply 220 V
 Conveyor Speed Variable
 Condition New
 Color Blue
 Machine Speed Variable
 Warranty one years

Machine Capacity Variable
Power Consumption 7 to 8 kw
Usage/Application Shrink Machine

Our technologically advanced **Semi Automatic Carton Taping Machine** are specifically designed for packaging of cartons. The thin walled or water proofing covering provided on the cartons acts as an additional reinforcement. It increases the strength of the cartons and enables them to sustain rough handling. Channel sets, filter assembly, fabricated body and rollers are some of the parts of the carton packaging machine. The adhesive tapes and films used for the sealing purpose are easily adjustable and impart secure sealing from both top and bottom of the carton. Depending on the size of the carton to be sealed its height can be adjusted for efficient performance. Carton sealing machine is used to seal cartons in industries such as home appliance, textile, food, general merchandise and many more

- Speed up to 6 - 8 bags per min.
- Manual feeding of bag/carton on the feeder conveyor
- Power 15 - 18 Kw, 3 phase. (Connected).
- Running 8 - 10 Kw.
- PLC controlled system
- Geared motor driven pre-pulling system for both packing rolls
- Heavy duty structure
- Shrink Tunnel Window Size (18" x 18") With Roller Conveyor.
- Sensor Based Technology for sealing purpose.
- Special pneumatically driven side sealing system, two sealers to provide both side sealing to make it all around seal
- Digital Temperature Controller PID type
- Belt Conveyor for Product Moving.
- Automatically Transfer of beg/carton after sealing into the tunnel
- Special double insulated chamber to reduce power losses.

Pneumatic Technology to be us