

contact@karmicaglobal.com https://www.karmicaglobal.com PO BOX 112030, DUBAI, UNITED ARAB EMIRATES +971-524819495

Product Name:
PVC Sleeve Label Applicators

Product Code: KGLOB10261027



Description:

PVC Sleeve Label Applicators

Technical Specification:

Output Per Hour Up to 300 BPM

Change Parts (A) Center Pillar (B) Worm (C) Cutter

Direction of Movement Left to Right

Container size 28mm -125mm dia., 320mm Height Max.

Length of Sleeve 30mm - 250mm

Thickness of Sleeve 0.035mm - 0.13mm

Label material PVC, PET, OPS

Sleeve roll outer dia 400mm Max.

Height of conveyor 860-910 mm

Electrical rating 1.5KW-2KW, AC380V, 50/60HZ, 3- phase

PVC Sleeve Label Applicators proficient, applying marks to the top or sides of the item with line velocities of up to 80 M/Min. Obviously, results of various shapes and sizes require their names to be connected in various ways.

Unique instrument modules are accessible to suit numerous regular applications and by mounting the name implement above, to the side or top scurvy underneath a transport, it is conceivable to accomplish the best marking position.

The other primary sort of name tool is the pneumatic cylinder implement. This kind will hold the mark on a spot by means of a vacuum.

Technical Specification:

Depends on container and label size

Specification can be altered as per customer specific requirement.