

| | |
|--|--|
| Product Name : Industrial Handheld Non-Contact Ink Jet Printer | Product Code : KGLOB10271001 |
|--|--|



Description :

Industrial Handheld Non-Contact Ink Jet Printer

Technical Specification :

Model Type Hand Held Inkjet Printer
 Print Method HP Cartridge
 Capacity 500 pieces per minute
 Automation Grade Semi-Automatic
 Condition New
 USB Available Yes

Which is a 4-in-1 Compact design, Zero Maintenance, 300 dpi high resolution, Mains/ Battery Powered SIX line (character height 1.2 to 12.7 mm) Printer & can be used on Porous / Non-Porous products to print B.No., Exp.Date, Time, Serial No., Logos, Scannable Bar Codes, etc. on labels, cartons, pouches, drums, containers, etc. It is fully programmable using the 4.3-inch full color Touch Screen LCD or with input from Pen Drive and is also capable of printing Multi-Segment / Grouped messages. It can also be mounted on stand for On-Line Printing.

| | |
|------------------|---|
| Display | 4.3" full color Touch Screen LCD with LED backlight. |
| Languages | English, Spanish, French, German, Chinese, etc. |
| Input Device | 800 x 480 Touch Screen LCD, Pen Drive. |
| Printable Images | Alphanumeric, Logo, Date/Time, Counter, Barcode, etc. UPCA, UPCE, |

| | |
|--------------------|---|
| | EAN13, EAN8, INT25, CODE39, CODE128, ENA128, PDF417, DATAMATRIX, QR |
| Printing Area | 1 to 6 lines of 2000 characters from 1.2 to 12.7 mm high. |
| Printing Direction | Adjustable at any angle within 360 degree |
| Message Capacity | Store upto 999 messages with Message Name. |
| Printing Speed | Max. 70 meters/min for 1 to 6 line printing at 300 dpi |
| Prints Using | Hewlett-Packard (hp) TIJ 2.5 Print-head for spraying ink |
| Print Distance | Max. 6 mm from substrate down or in front. |
| Inking Medium | 42 cc disposable pre-mix ink in Cartridge form with head. |
| Printing Medium | Solvent/Oil based inks (black, white, red, blue, yellow, etc.) |
| Ink Drying Time | Min. 5 seconds on plastics & laminates. |
| Impressions | Appx. 25 Lakh characters of 2 mm per cartridge of ink. |
| Operating Range | 10 ~ +38°C 10% - 80% RH, non-condensing. |
| Supply Voltage | 90 - 240 Vac, 50/60 Hz, 5 W |
| Battery Voltage | 16.8V lithium battery, 10 hours use / 20 hours standby |
| Dimensions | H130 x W128 x D20 mm |
| Weight | 1.2 Kg excluding cartridge & battery. |

This printer is fully Electronic without CORE system & does not have any air pump, viscosity control unit, filters, etc. & so there is no maintenance required (No AMC). It does not require separate make up or wash solution as everything is included in the disposable ink cartridges making it very user friendly for the Operator. The running / Printing cost is only about 4 Paise per impression (25 char).