

Product Name : Large Character Industrial Handheld Non-Contact Ink Jet Printer	Product Code : KGLOBAL0271002
--	---



Description :

Large Character Industrial Handheld Non-Contact Ink Jet Printer

Technical Specification :

Model Type Hand Held Inkjet Printer
 Automation Grade Automatic
 Color Output Monochrome
 Voltage 230 Vac
 Cartridges HP
 Certification CE,URL
 Battery Capacity 2600 mAH

Large Character Industrial Handheld Non-Contact Ink Jet Printer (50mm), which is a 4-in-1 Compact design, Zero Maintenance, 300-600 dpi high resolution, Mains/ Battery Powered TWENTY line (character height 1.2 to 50 mm) Printer & can be used on Porous / Non-Porous products to print B.No., Exp.Date, Time, Serial No. (AGMARK), Logos, Scannable variable Bar Codes, etc. on labels, cartons, pouches, drums, containers, etc. It is fully programmable using the 5-inch full color Touch Screen LCD or with input from USB Pen Drive and is also capable of printing Multi-Segment / Grouped messages. It can also be mounted on conveyor / stand for On-Line Printing.

Display	5" full color Touch Screen LCD with LED backlight.
---------	--

Languages	English, Turkish, Arabic, Chinese, etc.
Input Device	800 x 480 Touch Screen LCD, USB Pen Drive.
Printable Images	Alphanumeric, Logo, Date/Time, Counter, Barcode, etc. DATAMATRIX, QR, UPCA, UPCE, EAN13, EAN8, INT25, CODE39, CODE128, ENA128, PDF417, user added.
Printing Area	1 to 25 lines of 2000 characters from 1.2 to 50 mm high.
Printing Direction	Adjustable at any angle within 360 degree
Message Capacity	Store upto 10,000 messages with Message Name.
Printing Speed	Max. 60 meters/min for 1 to 12 line printing at 300-600 dpi
Prints Using	Hewlett-Packard (hp) TIJ 2.5 Print-head for spraying ink
Print Distance	Max. 6 mm from substrate down or in front.
Inking Medium	60 cc disposable pre-mix ink in Cartridge form with head.
Printing Medium	Solvent/Oil based inks (black, White, etc.)
Ink Drying Time	Min. 5 seconds on plastics & laminates.
Impressions	Appx. 40 Lakh characters of 2 mm per cartridge of ink.
Operating Range	0°C ~ 55°C, 10% - 80% RH, non-condensing.
Supply Voltage	90 - 240 Vac, 50/60 Hz, 5 W
Battery Voltage	16.8V lithium battery, 10 hours use / 20 hours standby
Dimensions	L235 x W140 x D120 mm
Weight	1.2 Kg excluding cartridge & battery.