

contact@karmicaglobal.com https://www.karmicaglobal.com PO BOX 112030, DUBAI, UNITED ARAB EMIRATES +971-524819495

Product Name: Ink Jet Printer

Product Code: KGLOB10271006



## **Description:**

Ink Jet Printer

## **Technical Specification:**

Print Method HP Cartridge
Capacity 500 pieces per minute
Automation Grade Semi-Automatic
Color & Page Single Color
Country of Origin Made in India
Type Inkjet
Uses Ink

Industrial Handheld Non-Contact Large Character Ink Jet Printer which is a Zero Maintenance, Battery Powered TWO line (character height 20 to 50 mm) Printer & can be used on Porous / Non-Porous products to print B.No., Exp.Date, Time, Serial No. on labels, cartons, pouches, drums, containers, etc. It is an ultra-compact portable and light inkjet printer equipped with a print-head with electromagnetic valves. It is battery operated and Bluetooth controlled & is fully programmable through PC with user-friendly software where it can print 2 lines Data & all Computer Fonts (local languages) at a very low price. It is also capable of printing Multi-Segment messages.

Display

2 digit LED display for Message No.

Input Device Printable Images Printing Area Printing Matrix Message Capacity

Printing Speed Prints Using

Print Distance Inking Medium Printing Medium

Ink Drying Time Impressions Operating Range Supply Voltage Dimensions Weight Bluetooth Communication with Computer Software.
Alphanumeric, Logo, Date/Time, Counter, etc.
1 to 2 lines of 120 char. each from 20 to 50 mm high.

 $5 \times 5$ ,  $5 \times 7$ ,  $10 \times 10$ ,  $10 \times 16$ ,  $16 \times 16$ 

16 memory location, 150 characters (5 × 7) per message, 75 characters (16 ×16) per message Max. 40 meters/min for 1 to 2 line printing 16 Nozzle electromagnetic valve Print-head for

spraying ink

Max. 25 mm from substrate.

150 cc ink in Cartridge form, 250 g ± 5 g

MEK / Solvent / Oil based inks (black, red\*, blue\*,

white\*, etc.)

Min. 10 seconds on plastics & laminates.

Appx. 4 million char. of 2 mm per cartridge of ink.  $5 \sim +45^{\circ}$ C, 10% - 90% RH, non-condensing.

12 V ± 5%, Charger: 12.6 V / 1A DC

212 x 135 x 120 mm

1.5 Kg ± 10 g including full ink cartridge & battery.

2/2