

Product Name :
 Motorized On-Line Pipe Coder

Product Code :
 KGLOB10271028



Description :

Motorized On-Line Pipe Coder

Technical Specification :

Usage/Application On Line
 Material Metal
 Automation Grade Automatic
 Voltage 230 Vac
 Power Consumption 25 watt
 Weight 50 kg
 Features standard feature

Motorized On-line Pipe Coder Model is a compact, fully automatic PLC based printer for 1 to 4 lines printing of ISI mark, Mfg. Dt., Company Name, Logos, etc. on all types of rigid or soft type PVC / Polyethylene / HDPE / PV pipes & tubes, etc. of diameter 20 mm to 200 mm during extrusion process. The message to be printed is very easily composed by just sticking the low-cost rubber / nylon stereotypes (easily changeable) on to the print wheel. The inking is in the form of rechargeable cartridge, so colour of printing can be changed easily by changing cartridge. The PLC has a bright LED display to set the printing repeat from 0.5 Meter to 25 Meters. It also displays the length of pipe extruded, no. of prints that have taken place & the linear speed of extrusion in meters / min.

Also, a production length can be set & it can give an alarm & relay signal after the preset length of pipe has been

extruded. (Free accessories include 1 Lit. Blue Ink, 1 Lit. Solvent, 6 mm Flat Rubber Character Set, Double Sided Tape & Ink Cartridge). These coders are ideal for Automatic On-Line Coding on various types of tubes & pipes during their extrusion process or as off-line printers also for manual printing.

Provision in the above Pipe Printer for continuous Coloured LINE from the bottom (Model PPC – 35 + Line – O) with Company Name & Data from the top.

Supply Voltage	230 Vac \pm 10%, 25 VA
Printing Area	1 to 4 Lines (max. 35 X 400mm)
Printing Repeat	Settable From PLC
Prints Using	Flat rubber / naylor Stereos.
Inking Medium	Rechargeable ink Cartridge
Printing Medium	Fast Drying Liquid ink (Black, Red, Blue, White* Golden/ etc)
Impressions	2,000 per 20 ml. Charge with continuous ink drip system
Weight (kgs)	45kgs