

Product Name :
Automatic Band Sealer Machines

Product Code :
KGLOB10271066



Description :

Automatic Band Sealer Machines

Technical Specification :

Usage/Application Pouch Sealing
Voltage 500 W
Driven Electric
Is It Portable Non Portable
Automation Grade Automatic

Automatic Band Sealer Machines keep feeding the filled pouches from one side of the machine. The Roller Bands will heat seal your pouch, move them forward & release them at the other end. No operator handling is required, thus making the sealing process very easy & fast. Optionally Embossing or printing of Exp. Dt., etc. will also take place simultaneously.

Features:

- Reliable sealing, high efficiency, low power consumption, small in size and elegant appearance
- Equipped with automatic temperature controlling device and a step less speed control system, for uniform heating and adjustable speed

-
- Ideal for all types of light to medium weight packets (upto 1-2 kg wt.)
 - Adjustable sealing speed of upto 20 packets per minute, which can be adjusted depending on pack size & operator capacity
 - Option of either 1 line embossing or 2 line hot roller ink printing of Exp. Dt., Mfg. Dt. or Product Name
 - Machine is robust model, with conveyor, which pulls the packets along, as they get sealed
 - Gas Flushing attachment for Nitrogen gas also available
 - Vacuum Suction Model also available

| | |
|-------------------|-------------|
| Power Supply | 220V/50 Hz |
| Consumption | 500 W |
| Sealing Speed | 0-12 M/m |
| Sealing Width | 6-15 mm |
| Film Thickness | 0.02-0.8 mm |
| Temp Range | 0-300° C |
| Conveyor Load | 5 Kgs |
| Machine size (cm) | 90x42x66 |
| Machine Weight | 45 Kg |